

Prepared By: CWS





Manufacturer: Rockwell Labs Ltd tel: 866 788 4101 EPA Est. No.: 73079-MO-1 Date: February 2005

1512 Taney St. fax: 816 283 3173

North Kansas City, MO 64116 USA emergency: 800 858 7378

Product Trade Name: D-Sect Custom Glueboard Common Name: insect glueboard

Composition: The glue is composed of mineral oils, aliphatic resins and synthetic rubber, treated with food flavorings. The product contains no pesticides.

SECTION I - HAZARDOUS INGREDIENTS

None. The glue and food flavorings are not known to be hazardous.

SECTION II - PHYSICAL PROPERTIES

Form: semi-solid Solubility: insoluble in water, soluble in organic solvents Viscosity: not known

Color: very pale yellow-brown % Volatiles by Volume (25 °C): ca. 0% pH: N/A

Odor: slight, sweet Vapor Pressure: considered insignificant Specific Gravity: 0.73 at 25 °C Vapor Density: considered insignificant

Evaporation Rate: N/A Water Reactivity: N/A

SECTION III - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Test Method): not known Flammable Limit: not known Auto Ignition Temp.: not known

Extinguishing Media: dry chemical, carbon dioxide or foam as appropriate for surrounding materials

Special Fire Fighting Procedures and Personnel Protection: Water or foam exposed to hot burning liquid may froth. Keep fire-exposed containers cool with water spray. Wear positive pressure self-contained breathing apparatus approved by MSHA/NIOSH.

Unusual Fire and Explosion Hazards: Dense smoke may be generated while burning. Carbon dioxide, carbon monoxide and other hydrocarbon combution products may be produced.

The fire and explosion hazards are considered very minor.

SECTION IV - HEALTH HAZARD DATA

The glue and food flavorings are not considered toxic via the oral, dermal or inhalation routes and not considered dermally irritating or

sensitizing. The glue is very tacky and can be difficult to remove from bodily hair - use vegeable oil to neutralize tack.

Primary Route(s) of Entry: dermal

Signs and Symptoms of Over-Exposure: not known

Acute and/or Chronic Effects: Ingredients are non-toxic if ingested in small quantities. Ingestion should be avoided.

Emergency and First Aid Procedures:

If in Eyes: Flush with water for at least 15 minutes and contact a physician if any persistent irritation results.

If Swallowed: Do not induce vomiting (to avoid aspiration). If more than a teaspoon is ingested contact a physician.

If on Skin: Wash with soap and water.
If Breathed: No known effects.

SECTION V - PERSONAL PROTECTION MEASURES

Ventilation: not required

Other Protective Measures: not required

SECTION VI - REACTIVITY DATA

Stability Under Normal Conditions: Stable

Hazardous Polymerization: Not known to occur Conditions to Avoid: sparks or flame

Incompatibility (Materials to Avoid): none known Hazardous Decomposition Products: carbon dioxide, carbon monooxide, other oxides

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in the Event Material is Spilled or Released: Inert absorbents may be used to contain spill.

Small Spill: Clean up the glue with vegetable oil followed by detergent and water.

Large Spill: Clean up the glue with mineral spirits and use precautions appropriate to that product. Follow by cleaning the area with detergent and water. Waste Disposal Procedures: Wastes resulting from use may be disposed of on site or at an approved waste disposal facility. Dispose of wastes in accordance with all Federal, State and Local laws.

SECTION VIII - STORAGE AND HANDLING PRECAUTIONS

Storage Temperature: Room temperature or cooler. Average Shelf Life: Two years in original container at room temperature.

Special Sensitivity (Heat, Light, Moisture): Avoid prolonged exposure to excessive heat.

Special Precautions to be Taken in Handling and Storage: Store in original container away from excessive heat and out of reach of children, pets or wildlife. Do not store near ignition sources.

SECTION IX - SHIPPING INFORMATION

DOT Shipping Name: None required DOT Hazard Classification: Non-Hazardous DOT Labels Required: None required Freight Classification: LTL Class 60

Warranty: The information provided in this Material Safety Data Sheet has been obtained from sources believed to be reliable. Rockwell Labs Ltd provides no warranties, express or implied, and assumes no responsibility for the accuracy and completeness of the data contained herein. This information is offered for your consideration and investigation. The user is responsible to ensure that they have all data relevant to their particular use.